




Quick Installation Guide

For Mac OS X


1 Connect to a Computer

Connect the adapter to a USB port on your computer using the USB cable provided.



2 Install Driver and Utility


- Insert the CD.
 Note: You can also download the driver and utility at www.tp-link.com.
- b. Browse the CD, go to Archer T4UHP > Mac
 OS X Driver, unzip the Mac OS X version.zip file and run the Installer.
- c. Follow the wizard to complete the installation.



3 Join a Wireless Network


Option 1: Via TP-LINK Utility

- a. Click (TP-LINK Wireless Configuration Utility) on the menu bar.
- b. Select your Wi-Fi network and enter the Wi-Fi password when prompted.



Option 2: Via Wi-Fi Protected Setup (WPS)

- a. Press the WPS button on your router.
- b. In 2 minutes, press and hold the WPS button on the adapter until the WPS progress screen appears.




c. When you are prompted "WPS Protocol Finished!", click **OK**.



MODEL NO. Archer T4UHP 7106506350 REV1.0.0

1 Connect to a Computer

Connect the adapter to a USB port on your computer using the USB cable provided.



Note


In Windows XP, a Found New Hardware Wizard window will appear when the adapter is detected. Please click Cancel

2 Install Driver and Utility

 a. Insert the CD and run the Autorun.exe from the pop-up Autoplay window.

Notes

- You can also download the driver and utility at www.tp-link.com.
- In some operating systems, the CD screen will pop up automatically. Otherwise, run the CD manually.
- Select Archer T4UHP and click Install Driver, then follow the InstallShield Wizard to complete the installation.



3 Join a Wireless Network

Option 1: Via Windows Wireless Utility


Click or (Network icon) on the task bar, select your Wi-Fi network, and click **Connect**.

Note: In Windows XP, you need to close the TP-LINK Utility before using the Windows Wireless Utility.



Option 2: Via TP-LINK Utility

Select your Wi-Fi network from the utility window and click **Connect**. The symbol indicates a successful connection.



Network TP-LINK_X

Option 3: Via Wi-Fi Protected Setup (WPS)

- a. Press the WPS button on your router.
- b. In 2 minutes, press and hold the WPS button on the adapter until the configuring screen appears.



c. When you are prompted "Successfully connected to the network by WPS!", click **OK**.



For more information, please visit our website http://www.tp-link.com

This USB Adapter can only be powered by computers that comply with Limited Power Source (LPS).

For Windows