



TP-LINK JetStream™

24-Port 10/100Mbps + 4-Port Gigabit L2 Managed Switch

TL-SL3428

Overview

TP-LINK JetStream™ gigabit L2 managed switch TL-SL3428 provides 24 10/100Mbps ports. The switch provides high performance, enterprise-level QoS, advanced security strategies and rich layer 2 management features. Moreover, the switch also comes equipped with 4 10/100/1000Mbps Ports and 2 combo gigabit SFP slots, expanding your network flexibly. TL-SL3428 is the cost-effective network solution for the ideal small and medium business.

TL-SL3428 has robust security and management features. The IP-MAC-Port-VID Binding and Access Control List (ACL) functions protect against broadcast storms, ARP and Denial-of-Service(DoS) attacks, etc. Quality of Service (QoS, L2 to L4) provides enhanced traffic management capabilities to move your data smoother and faster. Anymore, the easy-to-use web management interfaces, along with CLI, SNMP and RMON, mean faster setup and configuration with less downtime. For workgroup and departments requiring cost-sensitive Layer 2 Switch, TP-LINK JetStream™ L2 managed Switch TL-SL3428 provides you the ideal access-edge solution.

Layer 2 Features

- Link Aggregation Control Protocol (LACP)
- 4K VLAN
- GVRP (GARP VLAN Registration Protocol)
- Port Isolation
- STP/RSTP/MSTP
- IGMP Snooping

Quality of Service

- 4 priority queues
- Support IEEE 802.1P
- DSCP QoS
- Rate limit feature

Security Strategies

- IP-MAC-Port-VID Binding
- Access Control List (L2~L4 ACL)
- 802.1x and RADIUS Authentication
- Support DoS defend
- Port Security
- SSL and SSH encryptions

Management

- Web-based GUI
- Command Line Interface
- SNMP v1/v2c/v3
- RMON (1, 2, 3, 9 group)



- Details: <http://www.tp-link.com/support/Localesupport.asp>
- German/Austrian/Swiss users are not included



TP-LINK JetStream™ 24-Port 10/100Mbps + 4-Port Gigabit L2 Managed Switch

TL-SL3428

Secure Networking

TP-LINK TL-SL3428 provides IP-MAC-Port-VID Binding, Port Security, Storm control and DHCP Snooping which protect against broadcast storms, ARP attacks, etc. It integrates some typical DoS attacks to select. You can protect these attacks more easily ever than before. In addition, the Access Control Lists (ACL, L2 to L4) feature restricts access to sensitive network resources by denying packets based on source and destination MAC address, IP address, TCP/UDP ports and even VLAN ID. Moreover, the switch supports 802.1X authentication, which is used in conjunction with a RADIUS server to require some authentication information before access to the network is allowed. Guest VLAN function supports to enable the non-802.1X clients to access the specific network resource.

Advanced QoS features

To integrate voice, data and video service on one network, TL-SL3428 applies rich QoS policies. Administrator can designate the priority of the traffic based on a variety of means including IP or MAC address, TCP or UDP port number, etc, to ensure that voice and video are always clear, smooth and jitter free. In conjunction with the Voice VLAN the switch supporting, the voice applications will operate with much smoother performance.

Abundant Layer 2 features


For more application of layer 2 switches, TL-SL3428 supports a complete lineup of layer 2 features, including 802.1Q tag VLAN, Port Isolation, Port Mirroring, STP/RSTP/MSTP, Link Aggregation Control Protocol and 802.3x Flow Control function. Any more, the switch provides advanced features for network maintenance. Such as Loop Back Detection, Cable Diagnostics and IGMP Snooping. IGMP snooping ensures the switch intelligently forward the multicast stream only to the appropriate subscribers while IGMP throttling & filtering restrict each subscriber on a port level to prevent unauthorized multicast access.

Enterprise Level Management Features

TL-SL3428 is easy to use and manage. It supports various user-friendly standard management feature, such as intuitive web-based Graphical User Interface (GUI) or industry-standard Command Line Interface (CLI), either administration traffic can be protected through SSL or SSH encryptions. SNMP (v1/2/3) and RMON support enables the switch to be polled for valuable status information and send traps on abnormal events. In addition, integrated NDP/NTDP protocol, the switch supports to be managed by the commander switch through IP clustering function more easily.

Specifications

Physical Features & Performance

Product Picture		
Model		TL-SL3428
Physical Features		
Connector	10/100Mbps Base-T Ports	24
	10/100/1000Mbps Base-T Ports	4
	Combo Gigabit SFP Slots	2
	Console Port	1
Power Supply		100-240VAC, 50/60Hz
Fan Quantity		0
Certification		CE, FCC
Dimensions (W × D × H)		17.3 × 8.7 × 1.7 in. (440 × 220 × 44 mm)
		19-inch Rack mount Steel Case, 1U Height
Environment		Operating Temperature: 0°C~40°C (32°F~104°F), Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing, Storage Humidity: 5%~90% non-condensing
Performance		
Switch Capacity		12.8Gbps
Forwarding Rate		9.5Mpps
Mac Address Table		8k
Jumbo Frame		10KB

Software Features

L2 Switching Features

- **Link Aggregation**
 - Support static link aggregation
 - Support 802.3ad LACP
 - Up to 8 aggregation groups, containing 8 ports per group
- **Spanning Tree Protocol (STP)**
 - IEEE 802.1D Spanning Tree Protocol
 - IEEE 802.1S Multiple Spanning Tree Protocol
 - IEEE 802.1W Rapid Spanning Tree Protocol
 - STP Security: Loop Protect, TC Protect, BPDU Filter/Protect, Root Protect
- **Multicast**
 - Support IGMP Snooping V1/V2/V3, up to 256 groups
 - Support multicast VLANs, IGMP Immediate Leave, Unknown IGMP Throttling, IGMP Filtering, Static Multicast IP
- **VLAN**
 - Support IEEE802.1Q with 4K VLAN groups and 4K VIDs
 - Support Port VLAN, Protocol VLAN and MAC-based VLAN, Port Isolation
 - Support GARP/GVRP feature
 - Support management VLAN configuration
- **IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode**

Quality of Service (QoS)

- Support 802.1p CoS/DSCP priority
- Support 4 priority queues
- Queue scheduling: SP, WRR, SP+WRR
- Port/Flow- based Rate Limiting
- Voice VLAN assure voice applications much smoother performance

Advanced Security Strategies

- IP-MAC-Port-VID Binding
- Static/Dynamic Port Security (MAC-based)
- DoS defend feature
- Dynamic ARP Inspection
- 802.1x authentication
 - Support 802.1x port/MAC based authentication
 - Support Radius authentication and accountability
 - Guest VLAN
- Access Control List (ACL)
 - L2~L4 package filtering based on source and destination MAC address, IP address, TCP/UDP ports, 802.1p, DSCP, protocol and VLAN ID
 - Time based ACL
- Support Broadcast, Multicast and Unknown unicast Storm Control
- Secure web management through HTTPS and SSLv2/v3/TLSv1
- Secure remote command line interface (CLI) management with SSH v1/V2

Management

- Support Web-based GUI management mode
- Support Command Line Interface (CLI) through console port, telnet management mode
- SNMP v1/v2c/v3
- RMON (1, 2, 3, 9 groups)
- DHCP/BOOTP Client
- DHCP Snooping
- DHCP Option 82

- CPU Monitoring
- Port Mirroring (Many to One)
- Cable Diagnostics feature
- Ping/Tracert feature
- SNMP
- Integrated NDP/NTDP feature
- System Log

Ethernet Protocols

- IEEE 802.3i 10BASE-T
- IEEE 802.3u 100BASE-TX/FX
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3z 1000BASE-X
- IEEE 802.3av GVRP
- IEEE 802.3ad Link Aggregation
- IEEE 802.3x Flow control
- IEEE 802.1p QoS
- IEEE 802.1q VLANs / VLAN tagging
- IEEE 802.1v Protocol VLAN
- IEEE 802.1d Spanning Tree Protocol (STP)
- IEEE 802.1s Multiple Spanning Tree (MSTP)
- IEEE 802.1w Rapid Spanning Tree (RSTP)
- IEEE 802.1x Network Login Security

MIBs

- MIB II (RFC1213)
- Interface MIB (RFC2233)
- Ethernet Interface MIB (RFC1643)
- Bridge MIB (RFC1493)
- P/Q-Bridge MIB (RFC2674)
- RMON MIB (RFC2819)
- RMON2 MIB (RFC2021)
- Radius Accounting Client MIB (RFC2620)
- Radius Authentication Client MIB (RFC2618)
- Remote Ping, Traceroute MIB (RFC2925)
- Support TP-LINK private MIBs

Ordering Information

Host Switch	
Product Model	Description
TL-SL3428	JetStream™ 24-Port 10/100Mbps + 4-Port Gigabit L2 Managed Switch
SFP Modules	
Product Model	Description
TL-SM311LS	Gigabit SFP module, Single-mode, LC interface, Up to 10km distance
TL-SM311LM	Gigabit SFP module, Multi-mode, LC interface, Up to 550m distance
TL-SM321A	Gigabit WDM Bi-Directional SFP Module, single-mode, LC connector, TX:1550nm/RX:1310nm, 10km
TL-SM321B	Gigabit WDM Bi-Directional SFP Module, single-mode, LC connector, TX:1310nm/RX:1550nm, 10km
Media Converter	
Product Model	Description
MC210CS	Gigabit single-mode SC SFP Transceiver, up to 15Km, chassis mountable
MC200CM	Gigabit multi-mode SC SFP Transceiver, up to 550m, chassis mountable
MC220L	Gigabit SFP slot supporting mini-GBIC modules, chassis mountable
MC1400	14-slot power supply chassis for TP-LINK Media Converter, 19-inch rack-mountable