


How to upgrade TP-LINK Wireless Powerline Adapter

Notice:

- **Please verify the hardware version of your device so as to download the right firmware version.**
Wrong firmware upgrading may damage your device and void the warranty.



	Published Date	8/25/2010
	File Size	3.614 MB
	Operating System	Win98SE/Me/NT/2000/XP/2003/Vista/Windows 7/Linux
	Modifications and Bug Fixes	<ul style="list-style-type: none">• Fix some problems about IPSec.• Fix some bugs about IPoE.• Fix display problem on wireless page.• Add support to No-IP DDNS.• Time can be set manually or sync with PC.
	Notes	

- **After you downloaded the firmware from TP-LINK website, please use decompression software such as WinZIP or WinRAR to extract the firmware file to a folder;**
- **Do NOT turn off the power or cut down the Ethernet cable during upgrade process.**


Part 1: Login the Web management page of Powerline adapter

For Windows OS only

Step 1: Connect your **windows** computer to the Powerline adapter with Ethernet cable or wireless. Run the attached CD, Select your model and click the **Management Utility** (you can also download the PowerlineScan utility from TP-LINK website).



Step 2: The Utility will scan the whole network and show you all wireless Powerline adapters. **Please select the adapter which need to be configured** and click **Connect** to login the Web management page.



Note: If several wireless powerline adapters are displayed with the same Model No. on the screen, **but you can't separate them**. please refer to the MAC address to identify them. The device's MAC address can be found on the label at the bottom of the device.

Step 3: Type in the **Username** and **Password**, and click **OK**. Username and password are both **admin** unless you have changed it before.



For All Operating Systems

Step 1: Please plug only the wireless adapter to the power socket and connect your computer to the adapter.

Step 2: Manually configure a static IP address for your connection, wired or wireless. The IP address should be 192.168.1.x (2<x<254).

Step 3: Open the web browser and type **http://192.168.1.1** in the address bar, press the Enter button. Username and password are both **admin** unless you have changed it before.

Part 2: Upgrade the Firmware

Step 1: Click **System Tools** -> **Firmware Upgrade**, click the **Browse** button to choose the firmware you already extracted in the folder.

Firmware Upgrade

File: [Browse...](#)

Firmware Version: 3.12.11 Build 110915 Rel.40896n

Hardware Version: WR740N v4 00000000

[Upgrade](#)

Step 2: Click the **Upgrade** button. The device will reboot automatically after the upgrading has been finished. Please wait about 2 minutes.

Step 3: Click **Status**, verify that the router's firmware has been upgraded.

Status

Firmware Version: 3.12.11 Build 111130 Rel.55312n

Hardware Version: WR740N v4 00000000

Step 4: After upgrading, you should pair your Powerline adapters to build the Powerline network again.