

AC600 High Gain Wireless Dual Band USB Adapter





6 C C 4 4 4

E.



Option 2: Via the USB Extension Cable



2 Install Driver and Utility

product's Support page at www.tp-link.com.

Note: If your computer has a CD drive, you can also run the included CD to install the driver and utility.

b. Unzip the downloaded folder and run the Installer.pkg.

c. Follow the instructions to complete the installation.



- a. Download the driver and utility from this



3 Join a Wireless Network

- Option 1: Via TP-Link Utility
- a. Select the Site Survey tab of the pop-up utility window.
- b. Select your Wi-Fi network and click CONNECT. The connection status can be viewed on the Link Status screen.

SSID	8551D	Signal	Channel	Aube	Eng	Network Type
TP-Link_XXXX	72 - 10 -18 - 01 - 00 - 03	- 4	11	WPA2- PS	AES	Infrastructur
TP-Link_TEST	02 - 10 -18 - 01 - 00 - 02	50	38	WPA2- PS	AES	Infrastructur
TP-Link_0903	00 - 51 - E1 - 02 - 20 - 44	5	6	Open	NONE	Infrastructur
TP-Link_0001_9	00 - 10 - 18 - A9 - 5D - 8D	42	48	Open	NONE	Infrastructur

Option 2: Via Wi-Fi Protected Setup (WPS)

- a. Press the WPS button on your router.
- b. Within 2 minutes, press and hold the WPS button on the adapter until the WPS progress window appears.



c. When the "PBC-Get PBC profile successfully" message appears, it is complete.

Connect to a Computer

Option 1: Directly

87 For Windows





Option 2: Via the USB Extension Cable

Note: In Windows XP, a Found New Hardware Wizard window will appear when the adapter is detected. Please click Cancel.

2 Install Driver and WPS Tool

3 Join a Wireless Network

a. Insert the CD and run the Autorun.exe.

Note: You can also download the driver from this product's Support page at www.tp-link.com.

b. Select Archer T2UH and follow the steps to install the driver and WPS Tool. Note:

If you can't install the driver successfully, disable the antivirus software and firewall, then try again.



a. Click the network icon (*] or *) on the taskbar.

b. Select your Wi-Fi network, click Connect



Wireless Network Con

TP-Link XXXX TP-Link_XXXX_5G

🗹 Connect automatic

v	J

Option 1: Via Windows Wireless Utility

and enter the password when prompted.

	44
are availa	ble
nection	
	الي. ه الي. ه
cally	Connect
[(₁))	

Option 2: Via WPS Tool

a. Press the WPS button on your router.

b. Within 2 minutes, press and hold the WPS button on the adapter until WPS Tool opens.



c. When the "Success!" message appears, your computer is connected to Wi-Fi.

For detailed instructions, please refer to the User Manual from this product's Support page at www.tp-link.com.

For technical support and other information (\mathbf{U}) please visit http://www.tp-link.com/support or simply scan the QR code.

This USB Adapter can only be powered by computers that comply with Limited Power Source (LPS).

