



AV2000 2-port Gigabit Powerline Starter Kit

Smooth 4K Streaming and Gaming on Multiple Devices









Highlights

HomePlug AV2 Standard Compliant


The HomePlug AV2 standard creates high-speed data transfer rates of up to 2000Mbps to support all your online activities.

2000Mbps

HomePlug AV 600Mbps
HomePlug AV2

Gigabit Ethernet for Fast Connections

Two Gigabit Ethernet ports provide reliable high-speed wired connections for game consoles, smart TVs, STB and more.



Highlights

2 × 2 MIMO for More Throughput over Powerline

2 × 2 MIMO technology is like adding an extra lane on a highway. It establishes multiple simultaneous connections so you can enjoy 2× faster, more stable powerline speeds.

Power-Saving Mode

Power-Saving mode will automatically switch from its regular "Working" mode to "Power-Saving" mode reducing its energy consumption by up to 85%.







Features



Speed

- Ultra-fast Powerline Speed HomePlug AV2 standard compliant, high-speed data transfer rate of up to 2000Mbps, ideal for Ultra HD streaming and online gaming
- Multiple Gigabit Ports 2 Gigabit Ethernet Ports allow your TVs, game consoles or PCs to connect to the internet at high speeds



Ease of Use

- · Plug and play Plug and play, no configuration required
- No new wires No new wires, use existing electrical wiring to expand your home network
- TP-Link tpPLC Allows you to easily manage your network using the tpPLC Utility



Range

· 300-meter Range – Up to 300 meters/1000 feet over existing electrical wiring.



Security

· Pair Button – 128-bit AES encryption easily at a push of "Pair" button



Energy Saving

 Power Saving – Power Saving Mode helps reducing power consumption by up to 85%

Specifications


Hardware

- · Plug Type: EU
- · Standards and Protocols: HomePlug AV2, HomePlug AV, IEEE 1901, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
- · Power Consumption: Maximum: 5.8W

Typical: 5.6W

Standby: < 0.6W

- · Range: Up to 300 meters/1000 feet over existing electrical wiring
- · Interface: 2 × Gigabit Ethernet Port
- · Button: Pair Button
- · LED Indicator: Power, Powerline, Ethernet
- · Dimensions (W x D x H): 2.68 × 1.18 × 4.85 in. (68 × 30 × 123 mm)





For more information, please visit

http://www.tp-link.com/en/products/details/TL-PA9020-KIT.html

or scan the QR code left

Specifications are subject to change without notice. TP-Link Technologies Co., Ltd. Other brands and product names are trademarks of their respective holders. Copyright ©2017 TP-Link Technologies Co., Ltd. All rights reserved.

* Compatible with all HomePlug AV & AV2 Standard Powerline adapters.

Software

- · Modulation Technology: OFDM (PLC)
- · Encryption: Powerline Security: 128-bit AES

Others

- · Certification: CE, RoHS
- · Package Contents:
- 2 × Powerline Ethernet Adapter
- 2 × 2-meter Ethernet cable (RJ45)

Quick Installation Guide

· System Requirements:

Windows 2000/XP/2003/Vista, Windows 7/8/8.1/10, Mac, Linux

· System Requirements for tpPLC Utility:

Windows XP/Vista/7/8/8.1/10 and Mac OS X (10.7 or later)

· Environment:

Operating Temperature: 0°C~40°C (32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

^{*} Listed AV and Wi-Fi speeds refer to the theoretical maximum physical-layer data transfer rate. Actual data speeds vary and are influenced by the home's Wi-Fi/electrical/physical environment, and if adapters are placed on the same home circuit.