



# 8 Channel Network Video Recorder

MODEL: VIGI NVR1008H  
VIGI NVR1008



**1 HDD (10 TB Max)<sup>†</sup>**  
Up to 720 days of video<sup>‡</sup>



**Remote Management**  
**Dedicated VIGI app**



**Smart Detection**  
Configuration for Better  
Monitoring<sup>§</sup>



**Two-Way Audio**  
Listen and Talk in Real Time



**80 Mbps Bandwidth**  
Sufficient for Eight 4MP Cameras<sup>^</sup>



**Onvif**  
Promises Comprehensive  
Compatibility

## Overview

### VIGI Surveillance Solution

The VIGI professional surveillance system by TP-Link is dedicated to protecting the business that you've worked hard to build—whenever, wherever. Our outstanding functions, reliable quality guarantees, and simplified installation work together to ensure your business stays safe and sound.

## Highlight



#### 5MP Live View

Sharp image definition up to 5MP and an 8 channel display ensure you capture every detail, from every angle.



#### Simultaneous Playback

Replay the feed from up to 4 cameras\*\* at the same time, increase replay speed, and find events in the video schedule to easily review footage.



#### Secure Mass Storage

Automatically stores up to 10 TB of footage from connected cameras to secure your data for quick, convenient access.



#### Easy Management


Seamlessly manage the NVR and connected cameras via the VIGI app, VIGI Security Manager, or direct interface to customize them according to your specific needs.



#### Streamlined Setup

Simply connect your VIGI NVR and VIGI cameras to a switch, and plug in a monitor, then you're ready to go.

# Network Topology



1. POWER Outlet
2. AUDIO IN and AUDIO OUT for Two-Way Audio
3. HDMI and VGA Ports for Video Output
4. LAN Port for Ethernet Connection
5. Two USB Ports for Mouse, Keyboard, or Mobile Hard Disk Connection\*



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

For support and warranty, please visit <http://www.tp-link.com/support>

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

†HDD is not included.

^Calculations based on laboratory testing using a 3MP VIGI camera. Actual performance may vary according to amount of activity recorded, resolution, and other variables.

§Some features may experience suboptimal performance due to compatibility. For best performance, connect VIGI NVR to VIGI cameras.

\*Calculations based on laboratory testing using VIGI cameras.

\*A hard disk drive (not included) must be installed for operation.

\*\*Fewer or no channels may be available for playback if the total resolution is greater than 5MP.

Specifications are subject to change without notice. TP-Link and VIGI are trademarks of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright ©2020 TP-Link Technologies Co., Ltd. All rights reserved.

# Specifications

Models		VIGI NVR1008H	VIGI NVR1008
Video Input	IP Video Input	8-Channel	
		Up to 5 MP Resolution	
Network	Incoming Bandwidth	80 Mbps	
	Outgoing Bandwidth	60 Mbps	
Video Output	Recording Resolution	5 MP/ 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
	HDMI/VGA Output Resolution	1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1680 × 1050/60Hz, 1440 × 900/60Hz	
Decoding	Decoding Format	H.265+/H.265/ H.264+/H.264	H.264+/H.264
	Live View/Playback Resolution	5 MP/ 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
	Synchronous Playback	4-Channel	
	Capability	1-ch @ 5MP, 2-ch @ 2MP, 4-ch @ 720p	
Network Management	Network Protocols	TCP/IP, DHCP, DNS, NTP, UPnP	
Hard Disk	SATA	1 SATA Interface	
	Capacity	Up to 10 TB	
External Interface	Network Interface	1, RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface	
	USB Interface	2 × USB 2.0	
General	Power Supply	12V DC	
	Power	no more than 18 W	
	Power Consumption (without disk)	4.25 W	
	Power Consumption (with disk)	13.10 W	
	Working Temperature	-10–55 °C	
	Chassis	1U Chassis	
	Product Dimensions	246.2 × 148.2 × 45 mm	
	Product Weight	578.5g	