



Kasa Spot Wire-Free Camera

2-Camera System



KC310S2



Features



Crystal Clear Video

Sharp and clear 1080p video makes sure you never miss a thing.

Activity Zones

Control what notifications you receive by creating up to 4 custom activity zones, at no charge, around areas that are important to you.

Rechargeable Lithium Ion Battery

High capacity battery with optimized battery life for a longer and smarter experience.

Placement Freedom

Wire-Free or Wired, the wire-free camera gives you freedom to take the camera anywhere you want.

Wide Angle Field of View

130-degree wide angle lens lets you see more without the need for repositioning.

Two-Way Audio

Use crisp 2-way audio to communicate with the delivery person at your front door or use the camera's siren to scare away intruders.

IP65 Certified Weatherproof

IP65 rating ensures your device will be protected against rain and dust.

Watch from Anywhere

Watch live video at any time on your mobile devices with the free Kasa Smart app.

Night Vision

At night, the camera will detect activity up to 25 ft. away with night vision.

Notifications That Matter

With motion and sound detection, the Kasa Smart app alerts you of activity that matters and sends notifications straight to your smartphone.

Easy Install

Place your camera on the table or use the security mount to screw it into a hard surface. Easily configure the camera for the best angle.

Specifications

Camera

Video Resolution: 1080p Full HD
Night Vision: 850 nm IR LED up to 25 ft

Audio

Audio Communication: 2-way audio
Camera: Microphone and speaker

Video

Video Compression: H.264
Frame Rate: 15fps
Video Streaming: 1080p
Audio Compression: G.711

Activity Notifications

Input Trigger:
Motion detection, Audio detection
Output Notification: Push notification

System

Regulatory Certification:
Camera: FCC, IP65, RoHS, DOE, CEC, WERCS
Hub: FCC, RoHS
Battery: UL, RoHS, MSDS, UN38.3, WERCS
System Requirements: iOS 10+, Android 5.0+

Environment

Operating Temperature:
KC310: -20 °C-45 °C (-4°F-113°F)
KH310: 0 °C-40 °C (32°F-104°F)
Storage Temperature:
KC310: -20°C~45°C (-4°F~113°F)
KH310: -20 °C-70 °C (-4°F-158°F)
Operating Humidity:
KC310: 40%-80%RH, Non-condensing
KH310: 10%-90%RH, Non-condensing
Storage Humidity:
KC310: 40%~80%RH non-condensing
KH310: 5%-90%RH, Non-condensing

Hardware

Button: SYNC button
Indicator LED: System LED
Dimensions:
Camera: 65 x 63 x 63mm (L x W x H)
Hub: 91.62 x 82.5mm (D x H)
Input
Camera: 100-240VAC, 50/60Hz, 0.35A
Hub: 100-240VAC, 50/60Hz, 0.3A
Output
Camera: 5VDC, 2A
Hub: 9VDC, 0.6A

Network

Wireless Rate:
11Mbps(802.11b)
54Mbps(802.11g)
150Mbps(802.11n)
Frequency: 2.4GHz
Wireless Security:
WEP, WPA/WPA2-PSK
Security:
128 bit AES encryption with SSL/TLS

Package Contents

(2) Kasa Spot Wire-free Camera
(1) Kasa Spot Camera Hub
(1) USB-C Cable for Camera
(1) Ethernet Cable for Hub
(2) Wall Mount
(1) Power Adapter for Camera
(1) Quick Start Guide
(1) Power Adapter for Hub
(1) General Public License

