

Bluetooth 4.0 Nano USB Adapter











Nano Size

Highlights

Nano and Mighty

UB400 is highly portable and much smaller than a flash drive. Plug and play in Win8/8.1/10 systems to enjoy a wireless communication with Bluetooth-enabled devices.



Connect with Multiple Devices via Bluetooth 4.0

UB400 supports advanced Bluetooth 4.0 and enables wireless connectivity with a wide range of devices such as computers, printers, phones, headsets, speakers, keyboards, controllers, etc.




Features



- · Bluetooth 4.0 Backward compatible with Bluetooth® 2.0/2.1/3.0
- · Plug and Play Plug and play in Win8/8.1/10 systems



 Nano design – Small, unobtrusive design allows you to plug it in and forget it is even there



- Versatile Wireless Connectivity Enable wireless communication with Bluetooth-enabled computers, printers, phones, headsets, speakers, keyboards and more
- BLE Technology Bluetooth Low Energy technology for energy-saving wireless connectivity
- · Broad Operation Range Enjoy lossless music via your Bluetooth headset with a transmission distance of up to 10 m





For more information, please visit

https://www.tp-link.com/products/details/UB400.html
or scan the QR code left

©2019 TP-Link

*Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless coverage are not guaranteed and will vary as a result of 1) environmental factors, including building materials, physical objects, and obstacles, 2) network conditions, including local interference, volume and density of traffic, product location, network overhead, and 3) client limitations, including rated performance, location, connection quality, and client condition.

Specifications

Hardware

· Standard: Bluetooth 4.0

· Interface: USB 2.0

· Dimensions: 0.58 × 0.27 × 0.74 in (14.8 × 6.8 × 18.9 mm)

Others

Package Contents

Bluetooth 4.0 Nano USB Adapter UB400

Quick Installation Guide

Certification

FCC, CE, RoHS

· System Requirements

Windows 10/8.1/8/7/XP

Environment

Operating Temperature: 0°C~40°C (32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F ~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing