Quick Installation Guide

AC450 Wireless Nano USB Adapter MODEL NO. Archer T1U For more information, please visit our website http://www.tp-link.com



For Windows

Option 1: Via Windows Wireless Utility

Click ***** or ***** (Network icon) on the taskbar, select your Wi-Fi network, and click **Connect**.

Note: In Windows XP, if you have installed TP-LINK Utility, you need to close TP-LINK Utility before using Windows Wireless Utility.

For Mac OS X

Via TP-LINK Utility

A: Select the Site Survey tab of the pop-up utility window.

B: Select your Wi-Fi network and click CONNECT. The

7106506320 REV1.1.1

Option 2: Via TP-LINK Utility

Select your Wi-Fi network from the TP-LINK Utility window and click Connect. The symbol 2 indicates a successful connection.

Status WPS	Network Profile	Advanced SoftAP
Network Name(SSID)	Security 💌	Channel 🔻 Signal 💌
TP-LINK_A	WPA/WPA2-Personal	149 (5G)
	Connect automatically	Connect
34567_TEST	WPA/WPA2-Persona	I 149 (5G)
abcdef_0903	None	157 (5G)
AAAAA	None	161 (5G)



connection status can be viewed on the Link Status screen.

SSID	RSSID	Signal	Channel	Authe	Encr	Network Type
TP-LINK_A	72 - 10 - 18 - 01 - 00 - 03	26	149	WPA2-PS	AES	Infrastructure
34567_TEST	02 - 10 - 18 - 01 - 00 - 02	50	149	WPA2- PS	AES	Infrastructure
abcdef_0903	00 - 51 - E1 - 02 - 20 - 44	100	157	Open	NONE	Infrastructure
AAAAAA	00 - 10 -18 - A9 - 5D - 8D	42	161	Open	NONE	Infrastructure

©2015 TP-LINK