



24W 2-Port USB Car Charger

CP220

Highlights

- Exclusive Auto Detect & Smart Charging Technology
- 1.65X Fast Charging
- Intelligent Circuit Design
- Universial Compatibility
- Considerate design












Features







Exclusive Auto Detect & Smart Charging Technology

With auto detect and intelligent identification of connected devices, no matter devices with large battery like tablets (iPad, kindle,...) and smartphone (iPhone, Samsung Galaxy,...), or gadgets with tiny battery like smart wearable devices (Apple Watch, GoPro,...), it automatically delivers the fastest possible charge to maximize the compatibility

1.65X Fast Charging Compared with Your Original Charger

Charge 65% faster, save up to 40% charging time. Fully charging iPhone6s Plus takes 150 mins with CP220 while it takes 250 mins with an original Apple charger.

Intelligent circuit design

CP220 has a sophisticated circuit design with the latest safety features to protect your devices and power bank against short circuit, over voltage, over current, over charging, over discharging and over heating.

Features





Universial Compatibility

Compatible with smart devices running iOS, Android, Windows and most other USB-charged devices, such as GPS Navigator and Event Data Recorder. Besides, CP220 fully support and applicable to most of the current car models either in hardware or software compatibility

Considerate design

An unique crown design design ensures users insert CP220 in the right position and connect devices in the most convenient way. A dimmed LED indicator help visualize the connection status and does not distract you while driving.

Specifications

Hardware

Dimensions: 1.1 X 1.1 X 3.0 in.(27 x 28 x 77 mm)

Output Interface: 2 USB-A 2.0 Ports

Input Interface: 1 Car Cigarette Lighter

Input Voltage: Min. 12V DC; Max. 24V DC

Output Voltage: Total Output 5V/4.8A;

Charging Port Max. Output 5V/2.4A

Others

Package Contents: - 24W 2-Port USB Car Charger

- Quick Installation Guide

Certification: - CE, FCC, RoHS, EAC

Environment: - Operating Temperature: 0°C~40°C (32°F~104°F)

- Storage Temperature: -40°C~70°C (-40°F~158°F)

- Operating Humidity: 10%~90% non-condensing

- Storage Humidity: 5%~90% non-condensing

Comparison

CP220



CP230



CP250



24V Input:

Total Output: 5V/4.8A Output:

Charging Port Max. Output: 5V/2.4A

Input Interface: 1 Car Cigarette Lighter

Output Interface: 2 USB-A 2.0 Ports

Dimension: 1.1 X 1.1 X 3.0 in.(27 x 28 x 77 mm)

Smart Charging: Yes

Completed Safety Features:

Increased Compatibility: Yes 24V

Total Output: 5V/6.6A

Charging Port Max. Output: 5V/2.4A

1 Car Cigarette Lighter

3 USB-A 2.0 Ports

1.7 X 1.1 X 3.3 in.(44 x 29 x 85 mm)

Yes

Yes

Yes

24V

Total Output: 5V/4.8A

Charging Port Max. Output: 5V/2.4A

1 Car Cigarette Lighter

3 Cigarette Lighter Power Adapter, 2 USB-A 2.0 Ports

1.4 X 4.6 X 2.0 in.(35 x 117 x 50 mm)

Yes

Yes

Yes



For more information, please visit http://www.tp-link.com/en/products/details/?model=CP220 or scan the QR code left

www.tp-link.com

transformation, or adaptation without permission from TP-LINK Technologies CO., Ltd.