

150Mbps Wireless N Mini Pocket Router

TL-WR700N Datasheet

⦿ Features:

- Compatible with IEEE 802.11 n/g/b
- Wireless speed up to 150Mbps
- Foldable plugs*
- Travel size design, ideal for home or travel use
- Compact and portable, powerful wireless signal as well
- Perfectly compatible with almost all the 2.4GHz Wi-Fi devices
- Supports AP, Router, AP Client, Bridge, Repeater operation modes
- Supports WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions

* This product features only North American Type A plug




⦿ Description:

At 150Mbps, the mini pocket router creates an instant Wi-Fi hotspot by simply plugging in the Ethernet cable from your existing network or modem. It is a smart solution to efficiently expand your wireless network for the use of laptops, mobile phones, tablets or game consoles. The stylish cube design is small enough to fit into your pocket and plugs right into an electrical outlet without the hassle of using a power cord. The router is uniquely designed to provide exceptional wireless performance, bringing you extraordinary value at an affordable price.

◎ Specifications:

Hardware	
WIRELESS STANDARDS	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
FREQUENCY	2.4-2.4835GHz
INTERFACE	1 10/100Mbps WAN/LAN Port、 Reset Button
ANTENNA TYPE	On-Board
SIGNAL RATE	Up to 150Mbps(dynamic)
EIRP	<20dBm(EIRP)
RECEIVE SENSITIVITY	135M:-70dBm@10%PER 65M:-73dBm@10%PER 54M:-76dBm@10%PER 6M:-92dBm@10%PER
WIRELESS MODE	AP Mode, Router Mode ,Client Mode, Repeater Mode, Bridge Mode,
WIRELESS FUNCTIONS	Enable/Disable Wireless Radio, WDS Bridge, WMM,Wireless Statistics
WIRELESS SECURITIES	64/128/152-bit WEP / WPA / WPA2,WPA-PSK / WPA2-PSK
PORT FORWARDING	Virtual Server, Port Triggering, UPnP, DMZ
QUALITY OF SERVICE	WMM, Bandwidth Control
FIREWALL SECURITY	DoS, SPI Firewall; IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding
ENVIRONMENT	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
DIMENTIONS(L x W x H)	81mm x 71mm x 28mm (L x W x H)

◎ Diagram:



Package Contents:

- TL-WR700N
- Resource CD
- Quick Installation Guide
- RJ-45 Ethernet cable