

### **Bundled Firmware:**

[EAP110\\_V1](#), [EAP110\\_V2](#) [EAP110\\_V4](#)

[EAP115\\_V1](#), [EAP115\\_V2](#) [EAP115\\_V4](#)

[EAP225\\_V1](#), [EAP225\\_V2](#) [EAP225\\_V3](#)

[EAP225-Outdoor\\_V1](#)

[EAP110-Outdoor\\_V1](#) [EAP110-Outdoor\\_V3](#)

[EAP245\\_V1](#) [EAP245\\_V3](#)

[EAP115-Wall\\_V1](#) ( [EAP115-Wall](#) is suitable for EU version Only.)

[EAP225-Wall\\_V2](#)

[EAP235-Wall\\_V1](#)

[EAP230-Wall\\_V1](#)

[EAP320\\_V1](#) [EAP320\\_V2](#)

[EAP330\\_V1](#) [EAP330\\_V2](#)

### New Feature/Enhancement:

1. Added the feature that the system logs can be exported.
2. Changed the priority that non-administrator role cannot change the history data retention settings.
3. Optimized the UI of Statistics in Omada Controller.

### Bug Fixed:

1. Fixed the bug that the External Web Portal cannot authenticate successfully if the SSID of this portal has special characters.
2. Fixed the bug that the Cloud Access cannot be displayed normally in the low version of Firefox.
3. Fixed the bug that Omada Controller allow any user to read the files of controller.

4. Fixed the bug that controller will report an error when Top Usage data is empty.

Notes:

1. To use Omada Controller 3.2.X new features, you need to upgrade your EAP's firmware to the corresponding version.
2. Once upgraded to this version of Omada Controller, you will NOT able to downgrade to an earlier version.
3. Portal configuration will be lost after upgraded to Omada Controller 3.2.X from 2.4.X or earlier version.