

Bundled Firmware:

[EAP110_V1](#), [EAP110_V2](#) [EAP110_V4](#)

[EAP115_V1](#), [EAP115_V2](#) [EAP115_V4](#)

[EAP225_V1](#), [EAP225_V2](#) [EAP225_V3](#)

[EAP225-Outdoor_V1](#)

[EAP110-Outdoor_V1](#) [EAP110-Outdoor_V3](#)

[EAP245_V1](#) [EAP245_V3](#)

[EAP115-Wall_V1](#) ([EAP115-Wall](#) is suitable for EU version Only.)

[EAP225-Wall_V2](#)

[EAP235-Wall_V1](#)

[EAP230-Wall_V1](#)

[EAP320_V1](#) [EAP320_V2](#)

[EAP330_V1](#) [EAP330_V2](#)

New Feature/Enhancement:

1. Expand the number of Omada Controller's User Account to 500.
2. Optimize the External Portal Server to support URL with parameters.

Notes:

1. To use Omada Controller 3.2.X new features, you need to upgrade your EAP's firmware to the corresponding version.
2. Once upgraded to this version of Omada Controller, you will NOT able to downgrade to an earlier version.
3. Portal configuration will be lost after upgraded to Omada Controller 3.2.X from 2.4.X or earlier version.