

Bundle Omada Controller 3.2.5.

Bundled Firmware:

[EAP110 V1](#), [EAP110 V2](#) [EAP110 V4](#)

[EAP115 V1](#), [EAP115 V2](#) [EAP115 V4](#)

[EAP225 V1](#), [EAP225 V2](#) [EAP225 V3](#)

[EAP225-Outdoor V1](#)

[EAP110-Outdoor V1](#) [EAP110-Outdoor V3](#)

[EAP245 V1](#) [EAP245 V3](#)

[EAP115-Wall V1](#) ([EAP115-Wall](#) is suitable for EU verison Only.)

[EAP225-Wall V2](#)

[EAP235-Wall V1](#)

[EAP230-Wall V1](#)

[EAP320 V1](#) [EAP320 V2](#)

[EAP330 V1](#) [EAP330 V2](#)

New Feature/Enhancement:

1. Change the mechanism that when adopting an EAP, the Controller will retain the IP configuration of EAP in Standalone mode.
2. Extend the Max Associated Clients in Load Balance to 255.
3. Optimize the UI of Channel Utilization.
4. Optimize the authentication page of portal.
5. Optimize the UI of the portal that you cannot click Apply when you are uploading a photo.

Bug Fixed:

Fixed the bug that the page of MAC filter may not display all groups when there are more than 5 groups.

Notes:

1. For OC200 (UN) v1.0 only.
2. To use new features of OC200, you need to upgrade your EAP's firmware to the corresponding version.
3. Your device's configuration won't be lost after upgrading.