

Built-in Omada SDN Controller v5.8.38

1. Supported device models and firmware

- **EAP**

EAP690 HD EAP 670, EAP660 HD, EAP650, EAP650-Outdoor, EAP620 HD
EAP615-Wall, EAP610, EAP610-Outdoor
EAP265 HD, EAP230-Wall, EAP235-Wall, EAP225-Outdoor, EAP115-Wall
EAP245 V3, EAP225 V3, EAP225-Wall V2, and above versions
EAP115 V4, EAP110 V4, EAP110-Outdoor V3, and above versions

- **Switch**

TL-SX3016F, TL-SX3008F
TL-SG3452XP, TL-SG3452X, TL-SG3452P, TL-SG3452
TL-SG3428XMP, TL-SG3428MP, TL-SG3428XF, TL-SG3428X, TL-SG3428
TL-SG3210XHP-M2, TL-SX3206HPP
TL-SG2428P, TL-SG2218, TL-SG2008P, TL-SG2210MP
TL-SG3210 V3, TL-SG2210P V3.2, TL-SG2008 V3, TL-SL2428P V4, and above
versions

- **Gateway**

ER8411
ER7206 (TL-ER7206)
ER707-M2
ER605 (TL-R605) v1 and v2

2. New Features & Enhancements

1. Optimized startup time of the device.

Notes

1. This version of the Controller is fully applied to the Omada APP of version 4.6 or above.
2. Omada SDN Controller can only manage certain devices running the supported firmware. Please confirm that your device is compatible with the SDN Controller.
3. Your device's configuration won't be lost after upgrading.
4. This firmware is not cloud pushed, please download manually and upgrade locally.