

Version Info:

Firmware for S5500-4XHPP2XF(UN) 1.0.

Recommended Omada Controller V6.2.0.

New Features

1. Added NAT Traversal feature.
2. Supported Omada Config Tools V2.0.
3. Added support for Lightweight DHCPv6 Relay Agent (LDRA).
4. Extended L2PT functionality to support LLDP and 802.1X protocols.
5. Added IGMP Snooping VLAN SSDP Flood feature to ensure packets for multicast group 239.255.255.250 (commonly used for SSDP service discovery) are always flooded.
6. VLAN Isolation feature now supports configuration via SNMP.
7. Added CLI command to display STP Topology Change Notification (TCN) statistics per port.
8. Added statistics for ERPS ring port R-APS packet transmission and reception (RX/TX).
9. Add support for Type 8 (PBKDF2 with SHA-256) and Type 9 (Scrypt) password storage encryption type.
10. Add support for CPP (CPU protect policy).
11. Add support for MAC flapping.
12. Add support for packet capture.
13. Add support for ping and traceroute using domain names.
14. Add support for multiple RADIUS servers redundancy.
15. Add support for domain name RADIUS server.
16. Add support for RADIUS CoA & DM.
17. Add support for RADIUS accounting standard attributes Framed-IP-Address and Called-Station-ID.
18. Add support for IGMP auto-elect and TCN flood for IGMP.
19. Add support for Syslog protocol, custom UDP ports, and transmission over

UDP/TCP with DTLS or TLS.

20. Add support for LACP fast timeout.
21. Add support for deleting quadruple binding entries by port.
22. Add support for displaying user configuration information based on interface VLAN.
23. Add support for configuring DHCPv6 relay by port.
24. Add support for RadSec in 802.1X authentication.
25. Add support for log filtering based on keywords.
26. Add support for route unknown for IGMP Snooping and MLD Snooping.
27. Add support for SNMPv3 AES encryption.
28. Add support for displaying MAC status of the address through SNMP.
29. Add support for cloud firmware check and upgrade under standalone usage.
30. Add support for VLAN specific port isolation.
31. Add support for RSPAN.
32. Add support for DHCP Option 43.
33. Add support for DHCP filter per VLAN under standalone usage.
34. Add support for assigning IP address with 31-bit subnet mask in VLAN interfaces.
35. Add support for using domain name when configuring NTP server.
36. Add support for static IP binding with MAC address wildcards.
37. Add support for enabling/disabling Omada controller broadcast packets via CLI.
38. Add support for auto import/export IMPB entries.
39. Add support for SSH on/off on WebUI when controller state is abnormal.
40. Add support for configuring static DNS server under standalone usage.
41. Add support for pushing port names configured on Omada controller to the switch.
42. Add support for commands switching blacklist/whitelist for ACL under standalone usage.
43. Add support for obtaining temperature via SNMP.
44. Add support for IPv6 traffic matching via MAC ACL and MAC VLAN.

45. Add support for IMPBv6 working with IPv6 ACL.
46. Add support for cluster deployment.
47. Add support for combined ACL/IP ACL/IMPB with MAC ACL and MAC VLAN.
48. Add support for displaying tagged/untagged port types via "show vlan brief".
49. Add support for displaying port description in link up/down logs.

Enhancements

1. Supported common MAC address formats across all input fields.
2. Optimized ERPS convergence time on optical ports, achieving convergence within 50 ms.
3. Supported configuration of 802.1X authentication in MAB-only mode.
4. Added option to disable DNS Adoption to meet specific network management requirements.
5. Optimized fan status log reporting frequency.
6. Improved LLDP protocol compatibility.
7. Enhanced system self-healing capability to improve long-term stability.
8. Improved management link reliability.
9. Enhanced STP module reliability and overall spanning tree stability.
10. Optimize MAC group.
11. Optimize the initialization process and remove default username and password.
12. Optimize interaction between 802.1X and VLAN.
13. Optimize DDM configuration display.
14. Optimize log display for STP root bridge changes.
15. Improve packet capture functionality.
16. Improve FDB table display.
17. Optimized client alarm notifications in controller mode.
18. Optimize configuration for dropping unknown traffic.

19. Enable spanning tree by default.
20. Display total aggregated bandwidth for LAG.
21. Optimize log port description display.
22. Optimize dot1x authentication function.
23. Improve adoption stability in specific scenarios.
24. Improve spanning tree stability in specific scenarios.
25. Set loopback interface as SNMP global source interface.
26. Update default NTP servers.
27. Update OpenSSL library.
28. Disable HTTP access under standalone usage by default.
29. Add warning when configuring PortFast.
30. Uniform DHCP Vendor Class Identifier behavior.
31. Improve SNMP LLDP table compatibility.
32. Add loop detection log indication.
33. Support editing default OUI templates for voice VLAN.
34. Enable LLDP by default.

Bug Fixed

1. Fixed issues where SNMP nodes Q-BRIDGE-MIB and BRIDGE-MIB did not comply with protocol specifications.
2. Fixed port security anomalies in certain scenarios.
3. Fixed QoS anomalies in specific scenarios.
4. Fixed wired client list display issues in certain scenarios.
5. Fixed security vulnerabilities related to interaction with Omada Controller.
6. Fixed port authentication anomalies during upgrade.
7. Eliminated instability when multiple NTP servers are configured.
8. Fixed unstable SSH connections.

9. Fixed client authentication failures in specific scenarios.
10. Fixed aggregation group and port isolation linkage issues.
11. Fixed excessive DNS requests to NTP servers.
12. Fixed SNMPv3 security level access issues.
13. Fixed spanning tree anomalies in specific scenarios.
14. Fixed Remote Syslog compatibility issues.
15. Fixed spanning tree convergence under high client load.
16. Fixed sFlow configuration errors without description.
17. Fixed SNMPv3 user configuration errors.
18. Fixed RCE and DoS vulnerabilities.
19. Fixed Broken Access Control vulnerabilities.
20. Fixed low throughput in wireless speedtest scenarios.
21. Fixed high CPU usage when MAC table exceeds limits.
22. Fixed QinQ double-tag ping failure on UNI ports.
23. Fixed DHCP/ARP matching issue in MAC ACL and MAC VLAN.
24. Fixed abnormal SNMP QBridge FDB reporting on LAG ports.
25. Fixed 802.1X authentication issue with IP phone + PC daisy-chain scenario.

Others

None.