



8 Channel Network Video Recorder

MODEL: VIGI NVR1008H



1 HDD (16 TB Max)[†]
Up to 720 days of video[‡]



Remote Management
Dedicated VIGI app



Smart Detection
Configuration for Better
Monitoring[§]



Two-Way Audio
Listen and Talk in Real Time



80 Mbps Bandwidth
Sufficient for Eight 4MP Cameras[^]



Onvif
Promises Comprehensive
Compatibility

Overview

VIGI Surveillance Solution

The VIGI professional surveillance system by TP-Link is dedicated to protecting the business that you've worked hard to build—whenever, wherever. Our outstanding functions, reliable quality guarantees, and simplified installation work together to ensure your business stays safe and sound.

Highlight



8MP Live View

Sharp image definition up to 8MP and an 8 channel display ensure you capture every detail, from every angle.



Simultaneous Playback

Replay the feed from up to 4 cameras** at the same time, increase replay speed, and find events in the video schedule to easily review footage.



Secure Mass Storage

Automatically stores up to 16 TB of footage from connected cameras to secure your data for quick, convenient access.



Easy Management


Seamlessly manage the NVR and connected cameras via the web UI, NVR UI, VIGI app, and VIGI Security Manager. Customize the management system to suit your specific needs.



Streamlined Setup

Simply connect your VIGI NVR and VIGI cameras to a switch, and plug in a monitor, then you're ready to go.

Network Topology



1. Power Supply
2. AUDIO IN and AUDIO OUT for Two-Way Audio
3. HDMI and VGA Ports for Video Output
4. LAN Port for Ethernet Connection
5. Two USB Ports for Mouse, Keyboard, or Mobile Hard Disk Connection*



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

For support and warranty, please visit <http://www.tp-link.com/support>

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

†HDD is not included.

^Calculations based on laboratory testing using VIGI cameras. 80 Mbps is the maximum bandwidth available for managed cameras connected to the NVR.

§Some features may experience suboptimal performance due to compatibility. For best performance, connect VIGI NVR to VIGI cameras.

*Calculations based on laboratory testing using a 3MP VIGI camera. Actual performance may vary according to amount of activity recorded, resolution, and other variables.

*A hard disk drive (not included) must be installed for operation.

**Fewer or no channels may be available for playback if the total resolution is greater than 5MP.

Specifications are subject to change without notice. All brands and product names are trademarks or registered trademarks of their respective holders.

©2020 TP-Link

Specifications

Models	VIGI NVR1008H	
Video Input	IP Video Input	8-Channel
		Up to 8 MP Resolution
Network	Incoming Bandwidth	80 Mbps
	Outgoing Bandwidth	60 Mbps
Video Output	Recording Resolution	8 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF
	HDMI Output Resolution	1 Channel, Resolution: 3840x2160/30Hz,1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz
	VGA Output Resolution	1 Channel, Resolution: 1920x1080/60Hz,1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz
Decoding	Decoding Format	H.265+/H.265/ H.264+/H.264
	Live View/Playback Resolution	8 MP/5 MP/ 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF
	Synchronous Playback	4-Channel
	Capability	2-ch @ 8MP, 4-ch @ 4MP, 8-ch @ 2MP
Network Management	Network Protocols	TCP/IP, DHCP, DNS, NTP, UPnP
Hard Disk	SATA	1 SATA Interface
	Capacity	Up to 16 TB
External Interface	Network Interface	1, RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface
	USB Interface	2 × USB 2.0
General	Power Supply	12V DC/1.5A
	Working Temperature	-10~55°C
	Product Dimensions	246.2 × 148.2 × 45 mm
	Product Weight	578.5g