

Product information sheet	
Supplier's name or trade mark:	TP-Link, Tapo
Model identifier:	Tapo L930 (light strip of Tapo L930-5/10)
Type of light source	NA

Lighting technology	[HL ☐ /LFL T5 HF ☐ / LFL T5 HO ☐ /CFni ☐ /other FL ☐ /HPS ☐ /MH ☐ /other HID ☐ /LED ☒ /OLED ☐ /mixed ☐ /other ☐	Non-directional or directional:	[NDLS ☒ /DLS ☐
Mains or non-mains	[MLS ☐ /NMLS ☒	Connected light source(CLS)	[yes ☒ /no ☐
Colour-tuneable light source	[yes ☒ /no ☐	Envelope	[no ☒ /second ☐ /non-clear ☐
High luminance light source	[yes ☐ /no ☒		
Anti-glare shield	[yes ☐ /no ☒	Dimmable	[Yes ☒ /only ☐ / with specific dimmers/no ☐
On-mode power, expressed in W	3W	EEL class	[A ☐ /B ☐ /C ☐ /D ☐ /E ☐ /F ☐ /G ☒] ^(d)
Useful luminous flux (lm)& Beam angle correspondence	200 lm in [sphere ☒ /wide cone ☐ /narrow cone ☐	Correlated colour temperature type	4500K single
On-mode power (W)	2.5W	Standby power (W)	0.50W
Networked standby power for CLS (W)	0.50W	Colour rendering index	80

Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	1000	Chromaticity coordinates (x and y)	0.364,0.371
	Width	10		
	Depth	3		
R9 Colour rendering index		20	Survival factor	1.00
Lumen maintenance factor		0.96	Colour consistency in McAdam ellipses	6
displacement factor (cos ϕ_1)		/	Replacement claim (W)	/
Flicker metric (Pst LM)		/	Stroboscopic effect metric (SVM)	/
Rated L70B50 life (hours)		25000	Peak luminous intensity[cd]	[Yes ☐ /- ☒
Beam angle[°]		☒ N/A	Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage [W](LED and OLED mains)	☒ N/A
Spectral power distribution in the range 250 nm to 800 nm, at full-load		spectrum 1.0 = 4.325e+000mW/nm 1.2 1.0 0.8 0.6 0.4 0.2 0.0 380 480 580 680 780 wavelength (nm)		

