

# Media Converter

---

## Datasheet

### MC420L

10G SFP+ Media Converter



## Highlights

- 1 × 1G/2.5G/5G/10Gbps Auto-Negotiation RJ45 port supporting Auto-MDI/MDIX
- Auto-negotiation of Half-Duplex / Full-Duplex transfer mode
- Complies with IEEE 802.3an, IEEE 802.3ae, and IEEE 802.3aq
- Easy switching between 1G/10G and 2.5G optical port modes
- Optical port supports hot-swappable
- Maximum transmission distance depends on the inserted SFP+/SFP Module

## Overview

The MC420L is a versatile, high-performance media converter designed to bridge 10G/2.5G fiber and 10GBASE-T copper networks. Its standout feature is a user-selectable DIP switch that enables flexible selection of the optical port speed—1G/10G or 2.5G. This makes it a perfect solution for both seamlessly upgrading legacy gigabit infrastructure and deploying new multi-gigabit backbones.

With this multi-gigabit fiber converter, building long-range, point-to-point connections is effortless, making it ideal for network extensions across multiple buildings, remote surveillance, and automated factory equipment. The MC420L offers flexible installation options, either as a standalone desktop unit or mounted in a compatible multi-slot chassis (Omada MC1400). Easy-to-view front panel LEDs provide real-time network status, and the maximum transmission distance is determined by the specific SFP/SFP+ module used.

# Specifications

## Hardware Features & Performance

| Model                  |                        | MC420L   |
|------------------------|------------------------|--|
| General                | Standards              | IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3an, IEEE802.3z, IEEE802.3ae, IEEE802.3x, IEEE 802.3aq, IEEE 802.3cb  |
|                        | LED                    | PWR, FX Link/Act, TP Link/Act  |
|                        | Interface              | SFP+ port, RJ-45 jack  |
|                        | Twisted-Pair           | 1000BASE-T/2.5GBASE-T/5GBASE-T:<br>4-pair UTP/STP of Cat. 5e or above (max. 100 m)<br>10GBase-T:<br>4-pair UTP of Cat. 6 (max. 55m), 4-pair UTP of Cat. 6a (max. 100m), or 4-pair STP of Cat. 6 or above (max. 100m) |
|                        | Fiber & Wave Length    | Depends on the used SFP/SFP+ module  |
|                        | Power                  | External Power Adapter: 9V/0.6A  |
|                        | Max. Power Consumption | 5.26 W   |
|                        | Dimensions             | 3.7 × 2.87 × 1.06 in (94.5 × 73 × 27 mm)   |
|                        | Certifications         | CE, FCC, RoHS  |
| Physical & Environment | Operating Temperature  | 0 °C to 50 °C (32 °F to 122 °F)  |
|                        | Storage Temperature    | -40 °C to 70 °C (-40 °F to 158 °F)   |
|                        | Operating Humidity     | 10% to 90% RH non-condensing   |
|                        | Storage Humidity       | 5% to 90% RH non-condensing  |