

# Pan/Tilt AI Home Security Wi-Fi Camera

**Tapo C222**



## Person/Pet/Vehicle Detection

Baby Crying  
Detection

Smart AI  
Tracking


Ethernet/Wi-Fi  
Networking



## // Highlights

### Person/Pet Detection and Tracking

Accurately identifies people and pets, reducing false alerts and unnecessary notifications. The camera automatically follows the subject, keeping it within the field of view.



## Features



### Baby Crying Detection

Notifies you when your baby cries.



### 2K 4MP<sup>△</sup>

Provides more crisp details.



### Two-Way Audio

Communicate in real time through a built-in microphone and speaker.



### Customizable Block Zones

Set customizable block zones to keep private areas from being monitored.



### Ethernet/Wi-Fi Connection

Connect the security camera through Wi-Fi or the Ethernet port.



### Cloud Storage Supported<sup>‡</sup>

Store videos by using cloud storage services.



### Night Vision up to 40 ft

Provides a visual distance of up to 40 ft in total darkness.



### Local microSD Storage<sup>†</sup>

Store up to 512 GB of video on a microSD card<sup>†</sup>.

<sup>†</sup>microSD card purchased separately.

<sup>‡</sup>Subscribe for cloud storage at <https://www.tapocare.com>

<sup>△</sup>Compatible with Alexa and Google Assistant supported displays. User experience is dependent on the connected device's specifications.

For more information, please visit <https://www.tapocare.com>

All brands and product names are trademarks or registered trademarks of their respective holders. Specifications are subject to change without notice.


©2025 TP-Link

## // Specifications

Camera	Image Sensor	1/3.0" Progressive Scan CMOS Not Starlight Sensor
	Lens	Focal Length: 4.0mm±5% Aperture: F2.0±5% Field of View: 88.3° (Diagonal), 75.2° (Horizontal), 40.8° (Vertical)
	Night Vision	850 nm IR LED (40 ft / 12 m)
	Day/Night Switch	IR-Cut Filter with Auto-Switching
	Interface & Button	1× Ethernet Port 1× RESET Button 1× microSD Card Slot (Up to 512 GB)
Video & Audio	Maximum Resolution	2560 x 1440 px
	Frame Rate	15/20/25/30 fps (Default 15 fps, can be set up to 30 fps)
	Digital Zoom	12x
	Video Compression	H.264
	Live View	Yes
	Image Enhancement	3DNR WDR
	Audio Input & Output	Built-in Microphone and Speaker

<b>Video &amp; Audio</b>	Audio Communication	Two-Way Audio with Noise Cancellation
	Siren Volume	90 dB (Level measured at 4-inch/10-cm distance)
<b>Storage</b>	Local Storage	microSD Card Slot on Camera (Up to 512 GB)
	Cloud Storage	Tapo Care Cloud Storage Services (Subscription required)
<b>Detection &amp; Notification</b>	Sensor	/
	AI Detection	Motion Detection Person Detection Pet Detection Vehicle Detection Line-Crossing Detection Camera Tampering Baby Crying Detection Cat Meows Detection Dog Barks Detection Glass Break Detection
	Activity Zones	Yes *Only works with Motion, Person, Pet, and Vehicle Detection.
	Output Notification	System Notification System Notification with Snapshot (Tapo Care Services)
	Network Connectivity	Connect via Wi-Fi or Ethernet cable
<b>Network</b>	Wireless Connectivity	IEEE 802.11b/g/n, 2.4 GHz Wi-Fi

<b>Network</b>	Transmission Rate	11b: 11 Mbps 11g: 54 Mbps 11n: 72.2 Mbps
	Protocol	TCP/IP, DHCP, ICMP, DNS, NTP, HTTPS, TCP, UDP
	Ethernet Port	1× 100 Mbps RJ45 Port on Camera
	RTSP	Yes
	ONVIF	Yes
<b>Security</b>	Security	On-Device Machine Learning 128-bit AES Encryption with SSL/TLS WPA/WPA2-PSK/WPA3
<b>Power</b>	Power Source	9V DC Power Adapter
	Input Voltage	100-240 V, 50/60 Hz
	Output Voltage	9 V, 0.6 A (DC Power)
	DC Power Connector Size	Inside Ø: 2.1 mm Outside Ø: 5.5 mm
	Power Cord Length	1.5 m
	Typical Power Consumption	3.0 W
	Maximum Power Consumption	5 W

<b>General</b>	Certifications	CE/NCC/BSMI/NTRA/JRF/VCCI/KC/RCM
	Smart Integration	Google Assistant, Amazon Alexa, Samsung SmartThings, IFTTT
	Mounting Options	Tabletop Ceiling-Mounted
	Operating Temperature	0 °C ~ 40 °C (32 °F ~ 104 °F)
<b>General</b>	Storage Temperature	-20 °C ~ 60 °C (-4 °F ~ 140 °F)
	Operating Humidity	10%~90% RH, Non-condensing
	Storage Humidity	5%~90% RH, Non-condensing
	Mounting Screw Size	
	Dimensions	3.23 x 3.23 x 4.43 in (82.05 x 82 x 112.6 mm)
	Weight	7.1 oz / 200 g
	Package Contents	Tapo C222 Camera Power Adapter Quick Start Guide Mounting Anchors Mounting Screws Mounting Template Sticker Camera Base