

Solar-Powered Pan/Tilt Security Camera Kit

Tapo C630 KIT







i Wire-Free, Worry-Free, Solar-Powered

360° AI

Person/Pet/Vehicle Tracking Detection

See in Color, Day and Night | Capture

24/7 Continuous | Free Local microSD Storage (Up to 512 GB)†











Highlights

360° Al Tracking

The camera provides 360° horizontal coverage and 130° vertical coverage.

Accurately identifies and tracks people, pets, and vehicles, ensuring it focuses on what truly matters.





Highlights

Premium Features. Total Control. All in One App.

Secure and control your home anywhere, anytime with the Tapo app. View live footage, speak to visitors, share clips, and easily tailor

advanced settings.

Free Person/Pet/Vehicle Detection

Smart Al identifies people, pets, and vehicles, reducing false alerts and unnecessary notifications, which also extends battery life.

Customizable Activity Zones

Set up customized detection zones to be alerted only in areas where you wish to monitor and block out zones you want hidden.







Features



Wire-Free Design

Enjoy unparalleled security with the flexibility to monitor any space—no outlets required.



High-Efficiency Solar Charging

Just 45 minutes[§] of direct sunlight charges Tapo C630 for all-day use. No sun? No problem.



Free Person/Pet/Vehicle Detection

Smart Al identifies people, pets, and vehicles, reducing false alerts and unnecessary notifications, which also extends battery life.



Customizable Sound and Light Alarm

Record your voice and set the spotlight brightness to create an alarm that fits your needs.



Two-Way Audio

Talk and listen through the device with its integrated microphone and speaker.



Color Night Vision

Enhances your nighttime security by revealing vivid colors with the built-in dual spotlights.



24/7 Continuous Capture

Breaking the boundaries of typical battery-powered cameras, the camera enables 24/7 continuous recording.



Local and Cloud Storage

Store footage on a microSD card (up to 512 GB)[†] without a subscription, or use cloud storage[‡] for added convenience.



IP65 Weatherproof

Performs well even in harsh environments with rain and dust, ideal for outdoor scenarios.

†microSD card purchased separately. Actual storage capacity depends on the size of the microSD card used.

*Subscribe for cloud storage at https://www.tapo.com/tapocare/

§45 min of sunlight is based on standard environmental conditions (1000W/m2, 25°C, AM1.5) and specified working scenes (up to 100 events triggered per day). Actual required time of sunlight may vary. Actual charging power may vary based on installation location, weather conditions, temperature, and other environmental factors.

"The suitable operating temperature for the Solar Panel is -20°C to 45°C. The battery charging temperature should be maintained between 0°C and 45°C.

Specifications are subject to change without notice. All brands and product names are trademarks or registered trademarks of their respective holders. ©2025 TP-Link



Specifications

Camera	Image Sensor	1/2.7" Progressive Scan CMOS Sensor
	Lens	Focal Length: 4 mm ± 5% Aperture: F1.6 ± 5% Field of View: 105.4° (Diagonal), 88.0° (Horizontal), 46.0° (Vertical)
	Night Vision	850 nm IR LED Color Night Vision
	Day/Night Switch	IR-Cut Filter with Auto-Switching
	Lighting	2× Built-in Spotlights Motion Activiated, App-Controlled
	Interface & Button	1× POWER Button 1× RESET Button 1× microSD Card Slot (Up to 512 GB)
Solar Panel	Connection Capacity	A solar panel can only connect to one camera.
	Output Port	Type-C
Video & Audio	Maximum Resolution	3K 5MP (2880 × 1620 px)
	Frame Rate	15 fps
	Digital Zoom	13.5×
	Video Compression	H.264
	Live View	Yes



Video & Audio	Image Enhancement	3DNR WDR
	Audio Input & Output	Built-in Microphone and Speaker
	Audio Communication	Two-Way Audio with Noise Cancellation
	Siren Volume	78.9 dBA (Level measured at 10 cm distance) 60.4 dBA (Level measured at 300 cm distance)
Storage	Local Storage	microSD Card Slot on Camera (Up to 512 GB, Purchase Separately)
	Cloud Storage	Tapo Care Cloud Storage Services (Subscription required)
Detection & Notification	Al Detection	Motion Detection Person Detection Vehicle Detection Pet Detection
	Activity Zones	Yes
	Output Notification	System Notification System Notification with Snapshot (Tapo Care Services)
Network	Network Connectivity	Connect via Wi-Fi
	Wireless Connectivity	IEEE 802.11b/g/n, 2.4 GHz Wi-Fi
	Transmission Rate	11b: 11 Mbps 11g: 54 Mbps 11n: 72.2 Mbps
	Protocol	TCP/IP, DHCP, ICMP, DNS, NTP, HTTPS, TCP, UDP



Security	Security	128-bit AES Encryption with SSL/TLS WPA/WPA2-PSK
Power	Power Source	Solar Panel, Built-in Rechargeable Lithium-ion Battery
	Solar Panel Max Charging Voltage	5.2 V
	Solar Panel Max Charging Power	2.5 W
	Camera Adapter Input	100-240 V, 50/60 Hz (Not Included)
	Camera Adapter Output	5.0 V, 2.0 A (Not Included)
	Power Cord Length	USB Adapter Cable Length: 0.5 m (19.68 in.) Solar Panel Charging Cable Length: 0.25 m (9.84 in.) Solar Panel Extension Charging Cable Length: 3.8 m (149.61 in.)
	Camera Typical Power Consumption	0.828 W
	Camera Maximum Power Consumption	2.868 W
General	Smart Integration	Google Assistant, Amazon Alexa
	Weather Resistance	IP65
	Mounting Options	Wall-Mounted Eave-Mounted Pole-Mounted (Pole-mounting loops are not included.)



General	Operating Temperature	-20 °C ~ 45 °C (-4 °F ~ 113 °F)
	Storage Temperature	-40 °C ~ 60 °C (-40 °F ~ 140 °F)
	Operating Humidity	10% ~ 90% RH, Non-condensing
	Storage Humidity	0 ~ 90% RH, Non-condensing
	Mounting Screw Size	40-0 40-0 41-0 41-0 41-0 41-0 41-0 41-0
	Dimensions	Camera Dimensions: 141 x 128 x 84 mm (5.55 x 5.04 x 3.31 in.) Solar Panel Dimensions: 173.4 x 120.4 x 15.7 mm (6.83 x 4.74 x 0.618 in.)
	Weight	Camera: 15.13 oz / 429 g Solar Panel: 5.08 oz / 144 g
	Package Contents	Tapo C630 Camera × 1 Tapo A201 Solar Panel × 1 Tapo A201 Solar Panel Bracket × 1 Base Cover × 1 USB Adapter Cable × 1 Extension Wire × 1 Cable Zip Tie × 1 Mounting Screws and Anchors Mounting Template Stickers Quick Start Guide