



**Omada BE11000(US) / BE9300(EU)
Ceiling Mount Tri-Band
Wi-Fi 7 Access Point**


Model: EAP773

Product Overview

EAP773 unleashes Wi-Fi 7's full potential through its 10G PoE+ port, ideal for bandwidth-intensive environments such as offices, retail, MDUs, and hotels.

- **6-Stream Tri-Band Wi-Fi 7:** Up to 11.0 Gbps for the US and up to 9.3 Gbps for the EU.[†]
- **1× 10G PoE+ Port:** Future-proof your entire network with Wi-Fi 7.
- **Low Latency and Interference:** 320 MHz bandwidth, Multi-Link Operation, Multi-RUs, and 4K-QAM deliver high-performance connectivity.[‡]
- **Flexible Deployment and Easy Setup:** Supports 802.3at PoE or DC power supply for flexible installation with Omada SDN for one-click setup.
- **Advanced Features:** Supports centralized cloud management, PPSK, multiple portals, mesh, and seamless roaming.[§]
- **More Connections and Wider Coverage:** Supports 380+ concurrent connections** and covers up to 1,500 ft² (140 m²)* for reliable and extensive wireless connectivity.

Product Appearance




[†]The actual capacity depends on the wireless environment and client traffic and is generally less than the maximum number of client connections.

^{**}Coverage value is calculated based on laboratory testing. Actual coverage is not guaranteed and will vary as a result of client limitations and environmental factors.

Feature Descriptions

Omada Wi-Fi 7 Technology: Swifter, Smoother, Stronger

Featuring superb Wi-Fi 7 technologies including Multi-Link Operation, Multi-RUs, and 4K-QAM, Omada EAP773 significantly enhances throughput, connection stability, and concurrent capacity, ensuring faster and higher quality connections for more devices.



10G PoE+ Port for Optimized Wired Performance

The 10G port unlocks the full power of Wi-Fi 7, seamlessly handling 4K streaming, large file transfers, and high-density connections for remarkable performance. Compatibility with 802.3at PoE is ideal for flexible deployment.

Easy Setup via the Omada App or Web Browser

Omada SDN supports quick setup of EAP773 through automatic device identification and one-click adoption. Configure and manage on the go via the Omada app or web browser.

Boosted Network Security

Advanced security features include a secure guest network with up to 16× SSIDs, SMS login, WPA3-Enterprise encryption, and rogue AP detection, ensuring safe, reliable connectivity for both guests and business operations.

Cloud-Based Centralized Management

As part of Omada's unified SDN ecosystem, EAP773 works with Omada switches, gateways, and controllers. Businesses gain end-to-end visibility, automated optimization, zero-touch provisioning, and batch configuration—all managed from a single cloud interface.

Specifications

Hardware Specifications

Item	Description	
Wi-Fi Standards	6 GHz: IEEE 802.11ax/be 5 GHz: IEEE 802.11a/n/ac/ax/be 2.4 GHz: IEEE 802.11b/g/n/ax/be	
802.11be	Spatial Streams	<ul style="list-style-type: none"> 2.4 GHz: 2×2 Uplink/Downlink with 2 spatial streams 5 GHz: 2×2 Uplink/Downlink with 2 spatial streams 6 GHz: 2×2 Uplink/Downlink with 2 spatial streams Support MU-MIMO
	Frequency Bands	2.400 to 2.4835 GHz ISM 5.150 to 5.250 GHz U-NII-1 5.250 to 5.350 GHz U-NII-2A 5.470 to 5.725 GHz U-NII-2C 5.725 to 5.850 GHz U-NII-3/ISM 6.105 to 6.425 GHz U-NII-5 6.425 to 6.525 GHz U-NII-6 6.525 to 6.875 GHz U-NII-7 6.875 to 7.125 GHz U-NII-8 *Note: Country-Specific Restriction Apply
	Bandwidth	2.4 GHz: 20 MHz/40 MHz 5 GHz: 20 MHz/40 MHz/80 MHz/160/240 MHz 6 GHz: 20 MHz/40 MHz/80 MHz/160 MHz/320 MHz *Note: Country-Specific Restriction Apply
	Wireless Data Rate	2.4 GHz + 5 GHz + 6 GHz: 10777 Mbps <ul style="list-style-type: none"> 2.4 GHz: 8.6 Mbps to 688 Mbps (MCS0-MCS13, NSS=1 to 2, EHT20/40) 5 GHz: 8.6 Mbps to 4324 Mbps (MCS0-MCS13, NSS=1 to 2, EHT20/40/80/160/240) 6 GHz: 8.6 Mbps to 5765 Mbps (MCS0-MCS13, NSS=1 to 2, EHT20/40/80/160/320)
	Radio Technology	Uplink/downlink OFDMA (Orthogonal Frequency-Division Multiple Access)
	Modulation Type	4096-QAM, 1024-QAM, 256-QAM, 64-QAM, 16-QAM, QPSK, BPSK
	Frame Aggregation	<ul style="list-style-type: none"> A-MPDU (Aggregate MAC Protocol Data Unit) for Tx/Rx A-MSDU (Aggregate MAC Service Data Unit) for Tx/Rx

Item	Description	
	Others	<ul style="list-style-type: none"> • Preamble Puncturing • BSS Coloring • Multi-Link Operation (MLO) • TWT (Target Wake Time) • Maximal Ratio Combining (MRC) • Transmit Beamforming (TxBF) • Wi-Fi Protect Access 3 (WPA3) • Dynamic Frequency Selection (DFS) • Cycle Delay Diversity (CDD) • Cycle Shift Diversity (CSD) • Space-Time Block Coding (STBC) • Low-Density Parity Check (LDPC)
802.11ax	Spatial Streams	<ul style="list-style-type: none"> • 2.4 GHz: 2×2 Uplink/Downlink with 2 spatial streams • 5 GHz: 2×2 Uplink/Downlink with 2 spatial streams • 6 GHz: 2×2 Uplink/Downlink with 2 spatial streams • Support MU-MIMO
	Frequency Bands	2.400 to 2.4835 GHz ISM 5.150 to 5.250 GHz U-NII-1 5.250 to 5.350 GHz U-NII-2A 5.470 to 5.725 GHz U-NII-2C 5.725 to 5.850 GHz U-NII-3/ISM 6.105 to 6.425 GHz U-NII-5 6.425 to 6.525 GHz U-NII-6 6.525 to 6.875 GHz U-NII-7 6.875 to 7.125 GHz U-NII-8 *Note: Country-Specific Restriction Apply
	Bandwidth	2.4 GHz: 20 MHz/40 MHz 5 GHz: 20 MHz/40 MHz/80 MHz/160 MHz 6 GHz: 20 MHz/40 MHz/80 MHz/160 MHz *Note: Country-Specific Restriction Apply
	Wireless Data Rate	<ul style="list-style-type: none"> • 2.4 GHz: 8.6 Mbps to 574 Mbps (MCS0-MCS11, NSS=1 to 2, HE20/40) • 5 GHz: 8.6 Mbps to 2402 Mbps (MCS0-MCS11, NSS=1 to 2, HE20/40/80/160) • 6 GHz: 8.6 Mbps to 2402 Mbps (MCS0-MCS11, NSS=1 to 2, HE20/40/80/160) *Note: Country-Specific Restriction Apply
	Radio Technology	Uplink/downlink OFDMA (Orthogonal Frequency-Division Multiple Access)
	Modulation Type	1024-QAM, 256-QAM. 64-QAM, 16-QAM, QPSK, BPSK
	Frame Aggregation	<ul style="list-style-type: none"> • A-MPDU (Aggregate MAC Protocol Data Unit) for Tx/Rx • A-MSDU (Aggregate MAC Service Data Unit) for Tx/Rx

Item	Description	
	Others	<ul style="list-style-type: none"> • TWT (Target Wake Time) • MRC (Maximal Ratio Combining) • TxBF (Transmit Beamforming) • WPA3 (Wi-Fi Protect Access 3) • DFS (Dynamic Frequency Selection) • CDD (Cycle Delay Diversity) • CSD (Cycle Shift Diversity) • STBC (Space-Time Block Coding) • LDPC (Low-Density Parity-Check)
802.11ac	Spatial Streams	<ul style="list-style-type: none"> • 5 GHz: 2×2 Uplink/Downlink MU-MIMO with 2 spatial streams
	Frequency Bands	5.150 to 5.250 GHz U-NII-1 5.250 to 5.350 GHz U-NII-2A 5.470 to 5.725 GHz U-NII-2C 5.725 to 5.850 GHz U-NII-3/ISM *Note: Country-Specific Restriction Apply
	Bandwidth	5 GHz: 20 MHz/40 MHz/80/160 MHz
	Wireless Data Rate	<ul style="list-style-type: none"> • 5 GHz: 6.5 Mbps to 1733 Mbps (MCS0-MCS9, NSS=1 to 2, VHT20/40/80/160)
	Radio Technology	OFDM (Orthogonal Frequency-Division Multiplexing)
	Modulation Type	256-QAM, 64-QAM, 16-QAM, QPSK, BPSK
	Frame Aggregation	<ul style="list-style-type: none"> • A-MPDU (Aggregate MAC Protocol Data Unit) for Tx/Rx • A-MSDU (Aggregate MAC Service Data Unit) for Tx/Rx
802.11n	Spatial Streams	<ul style="list-style-type: none"> • 2.4 GHz: 2×2 MIMO with 2 spatial streams • 5 GHz: 2×2 MIMO with 2 spatial streams
	Frequency Bands	2.400 to 2.4835 GHz ISM 5.150 to 5.250 GHz U-NII-1 5.250 to 5.350 GHz U-NII-2A 5.470 to 5.725 GHz U-NII-2C 5.725 to 5.850 GHz U-NII-3/ISM *Note: Country-Specific Restriction Apply
	Bandwidth	20 MHz/40 MHz
	Wireless Data Rate	<ul style="list-style-type: none"> • 2.4 GHz: 6.5 Mbps to 300 Mbps (MCS0-MCS7, NSS=1 to 2, HT20/40) • 5 GHz: 6.5 Mbps to 300 Mbps (MCS0-MCS7, NSS=1 to 2, HT20/40)
	Radio Technology	OFDM (Orthogonal Frequency-Division Multiplexing)

Item	Description	
	Modulation Type	64-QAM, 16-QAM, QPSK, BPSK
	Frame Aggregation	<ul style="list-style-type: none"> A-MPDU (Aggregate MAC Protocol Data Unit) for Tx/Rx A-MSDU (Aggregate MAC Service Data Unit) for Tx/Rx
	Others	<ul style="list-style-type: none"> MRC (Maximal Ratio Combining) TxBF (Transmit Beamforming) DFS (Dynamic Frequency Selection) CDD (Cycle Delay Diversity) CSD (Cycle Shift Diversity) STBC (Space-Time Block Coding) LDPC (Low-Density Parity-Check)
Antenna	Wi-Fi	<ul style="list-style-type: none"> 2.4 GHz: 2 × 4 dBi (peak gain), onboard omnidirectional antennas 5 GHz: 2 × 5 dBi (peak gain), onboard omnidirectional antennas 6 GHz: 2 × 5 dBi (peak gain), onboard omnidirectional antennas <p><i>*Note: The gains above are the single-antenna peak gains.</i></p>
	IoT	<ul style="list-style-type: none"> Bluetooth: 1 × 5 dBi (peak gain), onboard omnidirectional antennas
Interfaces	<ul style="list-style-type: none"> 1 × 100M/1000M/2.5G/5G/10Gbps Multigigabit Ethernet Port (RJ45); PoE in 1 × 1 DC power interface: 12VDC 	
IoT	BLE 5.2, 1Mbps	
Memory	<ul style="list-style-type: none"> Flash: 1024Mbit DRAM: 8192Mbit 	
Button	1 × Reset button: Press the button for longer than 5 seconds to make the device restore to factory settings.	
Indicator	1 × blue system LED indicates on the front:	
	LED status	indication
	blue	Power-on status
	Flash twice and then stay blue	Initialization is completed
	Flashing blue	Firmware update
	flashing blue 5 times	reset the device
	Quickly flashing blue	Locate the device
Slowly flashing blue	The device is in an isolated state.	
Reliability	MTBF (Mean Time between Failure)	295992 hours at the operating temperature of 25°C (77°F)
Power Supply	Input	802.3at PoE+: 42.5 - 57 V, 0.6A 12VDC/2.5A
	Output	/
Power Consumption	<ul style="list-style-type: none"> 802.3at (PoE+): 25.4W, 2.4GHz radio 2×2, 5GHz radio 2×2, 6GHz radio 2×2, wired link rate can be up to 10 Gbps, etc. Idle mode: 11.1W (PoE) 	
Surge/Lightning Protection	Ethernet Ports: ±4 kV	

Item	Description	
ESD/EMP Protection	<ul style="list-style-type: none"> Air discharge: ±8 kV Contact discharge: ±4 kV <p>*Note: ESD/EMP Protection means Electrostatic Discharge/Electromagnetic Pulse Protection independently.</p>	
Tx Power	Maximum transmit power	CE (ERIP) <ul style="list-style-type: none"> 2.4 GHz: 20 dBm 5 GHz: 23 dBm in U-NII-1, 23 dBm in U-NII-2A, 28 dBm in U-NII-2C, 6 GHz: 23 dBm FCC (Conducted Power) <ul style="list-style-type: none"> 2.4 GHz: 25 dBm 5 GHz: 25 dBm in U-NII-1, 24 dBm in U-NII-2A, 24 dBm in U-NII-2C, 25 dBm in U-NII-3 6 GHz: 23 dBm <p>*Note: MIMO combined power, excluding antenna gains. The actual transmit power depends on local laws and regulations.</p>
	Minimum transmit power	CE (ERIP) <ul style="list-style-type: none"> 2.4 GHz: 6 dBm 5 GHz: 6 dBm in U-NII-1, 6 dBm in U-NII-2A, 6 dBm in U-NII-2C, 7 dBm in U-NII-3 6 GHz: 6 dBm FCC (Conducted Power) <ul style="list-style-type: none"> 2.4 GHz: 4 dBm 5 GHz: 4 dBm in U-NII-1, 4 dBm in U-NII-2A, 4 dBm in U-NII-2C, 4dBm in U-NII-3 6 GHz: 4 dBm <p>*Note: MIMO combined power, excluding antenna gains. The actual transmit power depends on local laws and regulations.</p>
	Adjustable power increment	1 dBm
Environment	Temperature	<ul style="list-style-type: none"> Operating: 0°C to +40°C (33.8°F to +104°F) Storage: -30°C to +70°C (-22°F to +158°F)
	Humidity	<ul style="list-style-type: none"> Operating: 10% to 90% (non-condensing) Storage: 5% to 90% (non-condensing)
	Altitude	<ul style="list-style-type: none"> Storage: up to + 2000 m (6561 feet) Operating: up to + 2000 m (6561 feet)
Unit	Dimensions (W×D×H)	<ul style="list-style-type: none"> Main Unit: 220 × 220 × 32.5 mm (8.7 × 8.7× 1.3 in.) Shipping Unit: 265 × 262 × 95 mm (10.4 × 10.3 × 3.7 in.)
	Weight	<ul style="list-style-type: none"> Main Unit: 0.73 kg (1.61 lb) Mounting Bracket: 0.05 kg (0.11 lb) Shipping Unit: 1.2 kg (2.6 lb)
	Mounting	<ul style="list-style-type: none"> Ceiling /Wall Mounting (Kits included) Junction Box Mounting (Kits included) T-Bar Mounting (Kits included)

Software Specifications

Item	Description	
Wireless Functions	Maximum number of BSSIDs	24 (8 on each band)
	Maximum number of associated STAs	380+
	Guest Network	Yes
	ACS (Automatic Channel Selection)	Yes
	Airtime Fairness	Yes
	Band Steering	Yes
	802.11 Rate Control	Yes
	Rogue AP Detection	Yes
	URL Filtering	Yes
	RF Scan	Yes
	WLAN Optimization	Yes
	WIDS/WIPS	No
	Lock to AP	Yes
	Rate Limit	<ul style="list-style-type: none"> • SSID Rate Limit • Client Rate Limit
	Load Balance	<ul style="list-style-type: none"> • Maximum Associated Clients • RSSI Threshold
MLO	<ul style="list-style-type: none"> • 2.4 GHz+5 GHz • 2.4 GHz+6 GHz • 5 GHz+6 GHz • 2.4 GHz+5 GHz+6 GHz 	
Roaming	<ul style="list-style-type: none"> • 802.11 k • 802.11v • 802.11r • Non-Stick Roaming • Ping-Pong Roaming Suppression • AI Roaming <p style="color: green; margin-top: 5px;">*Note: Only support Layer 2 Roaming currently.</p>	
Multicast/Broadcast Management	<ul style="list-style-type: none"> • Multicast-to-Unicast Conversion • ARP-to-Unicast Conversation • Multicast Filtering • Multicast/Broadcast Rate Limit 	

Item	Description	
	QoS (Quality of Service)	<ul style="list-style-type: none"> • WMM (Wi-Fi Multimedia) • DSCP (Differentiated Services Code Point) • U-APSD (Unscheduled Automatic Power Save Delivery)
Security and Authentication	ACL	
	MAC Filter	
	802.1X Authentication	
	MAC-Based Authentication	
	<ul style="list-style-type: none"> • None • Enhanced Open • WPA/WPA2/WPA3-Personal • WPA/WPA2/WPA3-Enterprise 	
	Radius Accounting	<ul style="list-style-type: none"> • PPSK without Radius • PPSK with Radius (Generic Radius with bound MAC/EKMS/Generic Radius with unbound MAC)
	Captive Portal	<ul style="list-style-type: none"> • No Authentication • Simple Password • Hotspot (Voucher / Local User / SMS / RADIUS / Form Auth) • RADIUS Server • External LDAP Server • External Portal Server • Pre-Authentication Access • Authentication-Free Client
	EAP Types	<ul style="list-style-type: none"> • EAP-TLS • EAP-TTLS • EAP-PEAP • EAP-CHAP • EAP-SIM • EAP-AKA • EAP-GTC • EAP-FAST • EAP-PEAP • EAP-MD5 • EAP-MSCHAPv2 • PEAPv0 • PEAPv1
Management methods	Omada Controller	<ul style="list-style-type: none"> • Omada Controller v5.15.24 and above • Omada Essential v5.15.24 and above
	App	Omada app v5.0
	Standalone Management	Yes

Item	Description	
	Standalone Mesh	No
	SSH	Yes
	SNMP	v1, v2c, v3
Operating Modes	AP	Yes
	Repeater	No
	Mesh	Yes
System Feature	System Log	Yes
	Reboot Schedule	Yes
	WLAN Schedule	Yes
	NTP (Network Time Protocol)	Yes
	Email Alerts	Yes
	Firmware Upgrade	Yes
	Restore & Backup	Yes
	LED Control	Yes
Network Features	VLAN	<ul style="list-style-type: none"> • SSID VLAN • Dynamic VLAN • Management VLAN
	Static IP / DHCP Client	Yes
	IPv4/IPv6	Yes
	LLDP (Link Layer Discovery Protocol)	Yes
	mDNS	Yes
	Tools	<ul style="list-style-type: none"> • Ping / Traceroute / DNSLookup / ARP Table • Packet Capture • Terminal

Standards Compliance and Certifications

Item	Category	Description
Standards compliance	IEEE Standards	<ul style="list-style-type: none"> • IEEE 802.11a/b/g/n/ac/ax/be • IEEE 802.11e/i/k/v/r • IEEE 802.1x/q • IEEE 802.3at • IEEE 802.3ab • IEEE 802.3bz • IEEE 802.3x
	Radio Standards	<ul style="list-style-type: none"> • ETSI EN 300 328 • ETSI EN 301 893 • EN 303 413 • EN 303 687 • EN 50385 EN50665 EN IEC 62311 • FCC Part 15E • FCC Part 15C • RSS-247, RSS-GEN • LP0002
	EMC standards	<ul style="list-style-type: none"> • EN 55032 • EN 55035 • EN 301489-1 • EN 301489-17 • EN 301489-19 • FCC Part 15B • ICES-003 issue7 • CNS 15936
	Safety Standards	<ul style="list-style-type: none"> • EN 62368-1 • IEC 62368-1 • CNS 15598-1
	Security Standards	<ul style="list-style-type: none"> • WPA-Personal/Enterprise • WPA2-Personal/Enterprise • WPA3-Personal/Enterprise • OWE
	RoHS	<ul style="list-style-type: none"> • Directive 2011/65/EU, Directive (EU) 2015/863 • EN IEC 63000: 2018
	Others	<ul style="list-style-type: none"> • Equipment Radio Regulations: 2008 (including amendments) • VCCI-CISPR 32
	Certifications	<ul style="list-style-type: none"> • Wi-Fi Alliance: Wi-Fi 7 (R1), Wi-Fi 6 (R2), Wi-Fi 6E, WPA3-R3, WPA3-Suite B, Enhanced Open Security • FCC/CE/NCC/VCCI/JRF/BSMI


RF Performance

Frequency Band	Wi-Fi Protocol & Bandwidth	MCS Index / Data Rate	EU/US Maximum Transmit Power (dBm) per transmit chain	Receiver Sensitivity (dBm) per receive chain	
2.4 GHz	802.11n, HT20	MCS0	14/22	-96	
		MCS7	14/22	-78	
	802.11n, HT40	MCS0	14/22	-93	
		MCS7	14/22	-75	
	802.11ax, HE20	MCS0	14/22	-96	
		MCS11	14/20	-66.5	
	802.11ax, HE40	MCS0	14/22	-93	
		MCS11	14/20	-64	
	5 GHz	802.11n, HT20	MCS0	22/22	-94
			MCS7	20/20	-75
802.11n, HT40		MCS0	22/22	-91	
		MCS7	20/20	-72	
802.11ac, HT20		MCS0	22/22	-94	
		MCS7	20/20	-75	
802.11ac, HT40		MCS0	22/22	-91.5	
		MCS9	19/19	-66	
802.11ac, HT80		MCS0	22/22	-89	
		MCS9	19/19	-63	
802.11ax, HE20		MCS0	22/22	-94	
		MCS11	18/18	-66	
802.11ax, HE40		MCS0	22/22	-91	
		MCS11	18/18	-64	
802.11ax, HE80		MCS0	22/22	-89	
		MCS11	18/18	-61	
802.11ax, HE160		MCS0	22/22	-86	
		MCS11	18/18	-60	
802.11be, EHT20		MCS0	22/22	-94	
		MCS13	17/17	-63	
802.11be, EHT40	MCS0	22/22	-90.5		


Frequency Band	Wi-Fi Protocol & Bandwidth	MCS Index / Data Rate	EU/US Maximum Transmit Power (dBm) per transmit chain	Receiver Sensitivity (dBm) per receive chain
		MCS13	17/17	-60
		MCS0	22/22	-88
	802.11be, EHT80	MCS13	17/17	-57.5
		MCS0	22/22	-85
	802.11be, EHT160	MCS13	17/17	-55.5
6 GHz	802.11ax, HE20	MCS0	17/21	-93
		MCS11	17/18	-65
	802.11ax, HE40	MCS0	17/21	-90
		MCS11	17/18	-62
	802.11ax, HE80	MCS0	17/21	-87.5
		MCS11	17/17	-59
	802.11ax, HE160	MCS0	17/21	-85
		MCS11	17/17	-58
	802.11be, EHT20	MCS0	17/21	-93
		MCS13	17/17	-63
	802.11be, EHT40	MCS0	17/21	-90
		MCS13	17/17	-60
	802.11be, EHT80	MCS0	17/21	-87.5
		MCS13	17/17	-57.5
	802.11be, EHT160	MCS0	17/21	-84
		MCS13	16/16	-55
	802.11be, EHT320	MCS0	17/21	-81.5
		MCS13	15/15	-52.5

Antenna Radiation Patterns


2.4 GHz



5 GHz




6 GHz



Package Contents


Item	Quantity
EAP773	1
Installation Guide	1
Mounting Kit	1

US:



*The accessories may vary by country/region. Please refer to the actual product.

EU:



*The accessories may vary by country/region. Please refer to the actual product.

Support Services

We are committed to providing you with comprehensive and reliable support services to ensure seamless experience with Omada products.

- Contact Support: <https://support.omadanetworks.com/#contact-us>
- Warranty Services: <https://www.omadanetworks.com/support/replacement-warranty/>

Revision History

Version	Date	Description
V1.0	2025-12-23	Initial release.

†Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless data throughput, wireless coverage, and connected devices are not guaranteed and will vary as a result of internet service provider factors, network conditions, client limitations, and environmental factors, including building materials, obstacles, volume and density of traffic, and client location.

‡Use of Wi-Fi 7 (802.11be) and its features including Multi-Link Operation (MLO), 320 MHz bandwidth, 4K-QAM, Multi-RUs, OFDMA, and MU-MIMO requires clients to also support the corresponding features.

§These features require the use of an Omada controller.

*Coverage is calculated based on laboratory testing. Actual coverage is not guaranteed and will vary as a result of client limitations and environmental factors.

**Actual capacity depends on the wireless environment and client traffic and is generally less than the maximum number of client connections.

Some models featured in this guide may be unavailable in your country or region. Visit TP-Link website for local sales information: <https://www.omadanetworks.com>. Specifications are subject to change without notice.

© 2025 TP-Link