

Unmanaged Switch

Datasheet

DS1016G

16-Port Gigabit Unmanaged Rackmount Switch



Highlights

- 16× 10/100/1000Mbps RJ45 ports
- Innovative energy-efficient technology saves power consumption
- Supports MAC address self-learning and auto MDI/MDIX
- Standard 19-inch rack-mountable steel case
- Isolation Mode allows one-click client traffic separation for higher security and performance
- Monitor and address loop-related issues within your network structure to prevent disruptions caused by looping
- Plug and Play. No configuration or central management required.*

Product Pictures



Specifications

Features & Performance	
	Model
Hardware Features	Standards and Protocols
	Interface
	Network Media
	Fan Quantity
	Physical Security Lock
	Power Supply
	Dimensions (W x D x H)
	Mounting
	Max. Power Consumption
	Max Heat Dissipation
Performance	Switching Capacity
	Packet Forwarding Rate
	MAC Address Table
	Jumbo Frame
Software Features	Advanced Features
	Transmission Method

Others	Certification	CE, FCC, RoHS
	Package Content	<ul style="list-style-type: none"> • DS1016G • Power Cord • Installation Guide • Rackmount Kits • Rubber Feet
Physical & Environment	Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
	Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
	Operating Humidity	10% to 90% RH non-condensing
	Storage Humidity	5% to 90% RH non-condensing

*Omada Unmanaged Switches do not support Omada SDN central management and cloud access. Some models featured in this guide may be unavailable in your country or region. Visit the Omada by TP-Link website for local sales information: <https://www.omadanetworks.com>. Specifications are subject to change without notice.
 © 2025 TP-Link