

Cable

Datasheet

SM5220-3M

3 Meter 10G SFP+ Direct Attach Cable

Highlights

- 10G SFP+ connector on both sides
- Drives 10 Gigabit Ethernet (3m distance)

Overview

With a passive twin-ax cable assembly of 3 meters and two SFP+ connectors on each side, SM5220-3M is suitable for short distances and offers a cost-effective way to connect within racks and across adjacent racks.



Specifications

Hardware Features & Performance		
Model		SM5220-3M
General	Product Dimensions	<ul style="list-style-type: none">• Plug: 2.26*0.53*0.34 in (57.5*13.55*8.55 mm);• Overall length: 118.11 in (3,000 mm)
	Max. Cable Length	3 m
	Data Rate	10 Gbps
	Conductor	Silver Plated Copper
Physical & Environment	Operating Temperature	0 °C to 70 °C (32 °F to 158 °F)
	Storage Temperature	-40 °C to 85 °C (-40 °F to 185 °F)
	Operating Humidity	10% to 90% RH non-condensing
	Storage Humidity	5% to 90% RH non-condensing

Some models featured in this guide may be unavailable in your country or region. Visit the Omada by TP-Link website for local sales information: <https://www.omadanetworks.com>. Specifications are subject to change without notice.